

WERT NANO PRO C3 5W40

Description	<p>Fully synthetic motor oil for petrol and diesel engines. Developed according to a revolution technology, based on new generation nano additives and carefully selected synthetic base oils to obtain the following criteria:</p> <ul style="list-style-type: none">– lower fuel consumption– low SAPS content– suitable for all DPF filters and modern catalyts– fast cold start– safe nanofilm at high temperatures and high loads– extended oil drain intervals– very good detergency and dispersion– very strong protection against foaming, wear and corrosion																				
Application	<p>This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the latest VW 504.00/507.00 requirements, in practice also called VW Longlife III oils.</p>																				
Performance Level	<p>ACEA C3 Approved VW 505.00/505.01 MB-Approval 229.51 BMW LL-04 Porsche C30</p>																				
Typicals	<table><tr><td>Density at 15 °C, kg/l</td><td>0,851</td></tr><tr><td>Viscosity -30 °C, mPa.s</td><td>5950</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>69,20</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>12,90</td></tr><tr><td>Viscosity Index</td><td>171</td></tr><tr><td>Flash Point COC, °C</td><td>230</td></tr><tr><td>Pour Point, °C</td><td>-42</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>8,2</td></tr><tr><td>Sulphate Ash, %</td><td>0,67</td></tr><tr><td>HTHS</td><td>3,59</td></tr></table>	Density at 15 °C, kg/l	0,851	Viscosity -30 °C, mPa.s	5950	Viscosity 40 °C, mm ² /s	69,20	Viscosity 100 °C, mm ² /s	12,90	Viscosity Index	171	Flash Point COC, °C	230	Pour Point, °C	-42	Total Base Number, mgKOH/g	8,2	Sulphate Ash, %	0,67	HTHS	3,59
Density at 15 °C, kg/l	0,851																				
Viscosity -30 °C, mPa.s	5950																				
Viscosity 40 °C, mm ² /s	69,20																				
Viscosity 100 °C, mm ² /s	12,90																				
Viscosity Index	171																				
Flash Point COC, °C	230																				
Pour Point, °C	-42																				
Total Base Number, mgKOH/g	8,2																				
Sulphate Ash, %	0,67																				
HTHS	3,59																				