

## WERT PROTECT 10W40

### Description

Semi synthetic motor oil for petrol and diesel engines. Developed according to a revolution technology, based on new generation additives and carefully selected base oils to obtain the following criteria:

- lower fuel consumption
- fast cold start
- extended oil drain intervals
- very good detergency and dispersion
- very strong protection against foaming, wear and corrosion

### Application

This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters.

### Exceed performance Level

API SL/CF  
ACEA A3/B3 A3/B4  
MB-Approval MB 229.51  
BMW Longlife-04  
PSA PEUGEOT CITROEN B71 2294 & B71  
2300 VW 502.00/505.00  
FIAT 9.55535-D2  
MIL-L-2104 D

### Typicals

Density at 15 °C, kg/l	0,851
Viscosity -30 °C, mPa.s	5950
Viscosity 40 °C, mm <sup>2</sup> /s	69,20
Viscosity 100 °C, mm <sup>2</sup> /s	15,50
Viscosity Index	142
Flash Point COC, °C	230
Pour Point, °C	-42
Total Base Number, mgKOH/g	9,2
Sulphate Ash, %	0,67