

WERT NANO FLEET SHPD 5500 15W40

Description

Semi-synthetic heavy diesel SHPD engine oil. Developed according to a revolution technology, based on new generation nano additives and carefully selected synthetic base oils to obtain the following criteria:

- lower fuel consumption
- fast cold start
- safe nanofilm at high temperatures and high loads
- extended oil drain intervals
- very good detergency and dispersion
- very strong protection against foaming, wear and corrosion

Application

This engine oil is developed for heavy diesel engines, working even under severe operating conditions. This product is suitable to use in Euro 4, Euro 3, Euro 2 engines.

Exceed Performance Level

API CI-4/SL
ACEA A3/B3, A3/B4, E7
Meets the requirements of
MB 228.3; 229.1
MAN M3275
Volvo VDS-3
MTU Type 2; Deutz DQC III-10
Mack EO-N, EO-M plus; Renault
RLD, RLD-2
Cummins CES 20076,77,78
Caterpillar ECF-2, 1a
Global DHD-1, JASO DH-1

Typicals

Density at 15 °C, kg/l	0,876
Viscosity -25 °C, mPa.s	6900
Viscosity 40 °C, mm ² /s	99
Viscosity 100 °C, mm ² /s	15,2
Viscosity Index	141
Flash Point COC, °C	226
Pour Point, °C	-39
Total Base Number, mgKOH/g	14,2
Sulphate Ash, %	1,48